


# Material Lifts

## Superlift Contractor™

### Specifications



#### Models

#### Measurements

##### Working height:

- standard forks - forks down
- standard forks - forks up
- adjustable forks - forks down
- adjustable forks - forks up
- boom\*\*

<b>A</b>	Height - stowed
<b>B</b>	Length - stowed
<b>C</b>	- operating
<b>D</b>	Width - stowed*
	- with stabilizers lowered

#### Productivity

##### Load capacity:

- 14 in (36 cm) load center
- 24 in (61 cm) load center
- 42 in (107 cm) load center

<b>E</b>	Ground clearance
	Load height minimum

#### Power

##### Average cranks - per length unit

- Standard winch - carriage moving
- Standard winch - mast moving

#### Weight

#### SLC-18

#### US Metric

- 16 ft 9 in 5.10 m
- 18 ft 6 in 5.64 m
- 16 ft 9 in 5.10 m
- 18 ft 6 in 5.64 m
- 17 ft 9 in 5.41 m

7 ft 2 in	2.18 m
2 ft 10 in	.86 m
6 ft 1 in	1.85 m
2 ft 7.5 in	.80 m
5 ft 6 in	1.68 m

650 lbs	295 kg
425 lbs	193 kg
160 lbs	73 kg
2 in	.05 m
6 in	.15 m

12.5/ft	41/m
5.5/ft	18/m

307 lbs	139 kg
---------	--------

\* Outside dimensions.  
 \*\* Measured from ground to bottom of shackle.  
 \*\*\* Length/Width/Depth, from end of carriage and outside of forks

## Features

### Standard Features

### Measurements

#### SLC-18

- 18 ft 6 in (5.64 m) maximum lifting height
- Up to 650 lbs (295 kg) lift capacity

### Productivity

- Standard forks
- Heavy-duty design
- Strong, lightweight aluminum telescoping mast
- Single door access
- Quick set up requires no tools
- Interchangeable load handling attachments
- Non-marking 4 in (10 cm) front casters and 5 in (13 cm) rear casters with side brakes
- Rear transport wheel assembly
- Glide rails allow easy loading and unloading, on or off a vehicle, for transport
- Hold-down bar secures mast assembly during transport
- Captive stabilizer set (standard on SLC™-18, -24)
- Winch locks load in place

### Power

- One speed manual winch



### Genie United States

6464 185th Ave. NE  
Redmond, WA 98052  
Telephone +1 (425) 881-1800  
Toll Free in USA/Canada +1 (800)-536-1800  
Fax +1 (425) 883-3475

### Distributed By:

Effective Date: November, 2018. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2018 Terex Corporation.