

Specifications

Models

Measurements

A Height - stowed ^{1, 2, 3}
maximum forks down
maximum forks up

Standard Base

B Length - stowed
operating

C Width: outside

Weight - standard caster options
pneumatic caster options

Straddle Base

Length - stowed
operating

Width - stowed ⁴
maximum ⁴
maximum inside

Weight - standard caster options
pneumatic caster options
4-point caster option A
4-point caster option B

Counterweight Base

Length - operating

Width - stowed ⁴
maximum ⁴
maximum inside

Weight - standard caster options

Productivity

Load height minimum (forks down)
- Straddle Base

Ground clearance - center ^{1, 2, 3}
--

Average cranks - standard winch

Fork length

Fork width - outside

Fork width - inside

Load platform length

Load platform width

Load capacity at

14 in (36 cm) load center

Boom length

Boom attachment points

Power

Average cranks - per length unit

Standard winch - carriage moving

Standard winch - mast moving

GL-8

US Metric

5 ft 7.5 in	1.72 m
8 ft 3 in	2.51 m
10 ft .5 in	3.06 m

1 ft	.30 m
------	-------

2 ft 10.75 in	.88 m
---------------	-------

2 ft .75 in	.63 m
-------------	-------

132 lbs	60 kg
---------	-------

136 lbs	62 kg
---------	-------

1 ft 7.25 in	.49 m
--------------	-------

3 ft 7 in	1.09 m
-----------	--------

2 ft 4.75 in	.73 m
--------------	-------

3 ft 7.5 in	1.10 m
-------------	--------

3 ft	.91 m
------	-------

145 lbs	66 kg
---------	-------

149 lbs	68 kg
---------	-------

158 lbs	72 kg
---------	-------

160 lbs	73 kg
---------	-------

2 ft 4.5 in	.72 m
-------------	-------

2 ft 4.75 in	.73 m
--------------	-------

3 ft 7.5 in	1.10 m
-------------	--------

3 ft	.91 m
------	-------

411 lbs	186 kg
---------	--------

3.5 in	.09 m
--------	-------

2.0 in	5.1 cm
--------	--------

.75 in	.02 m
--------	-------

11.5/ft	38/m
---------	------

1 ft 10.5 in	.57 m
--------------	-------

1 ft 8.5 in	.52 m
-------------	-------

13 in	33 cm
-------	-------

1 ft 11 in	.58 m
------------	-------

1 ft 10 in	.56 m
------------	-------

400 lbs	181 kg
---------	--------

20.19 in	51 cm
----------	-------

13.25/19 in	34/48 cm
-------------	----------

14/ft	46/m
-------	------


6.5/ft	21.3/m
--------	--------

¹ The 10 in pneumatic rear wheel option will add 1 in (2.5 cm) to these specifications.

² The counterweight base will add 1 in (2.5 cm) to these specifications.

³ The 4-point caster option B will add 1 in (2.5 cm) to these specifications.

⁴ Outside dimensions.



Features

Standard Features

Measurements

GL-8

- 10 ft .5 in (3.06 m) maximum lifting height
- Up to 400 lbs (181 kg) load capacity

Productivity

- Portable and compact design
- Rolls easily through a single door
- Durable standard steel forks
- 8 in (20 cm) non-marking rear wheels and 2 in (5 cm) dual wheel front swivel casters (standard and straddle base only)
- 5 in (12 cm) rear swivel casters with side brakes and 4 in (10 cm) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

Power

- Standard winch
- Reversible winch handle for easy storage



* Winch operates while ladder is in use or stowed

Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By:

Effective Date: August, 2020. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2020 Terex Corporation.