

## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



### Easy start with reduced speed

Used with starting a hole, speed is reduced by half using the Smart Start® button, which reduces vibration.

- Smooth start with normal fuses
- Dry and wet drilling
- Elgard™
- Smart Start®

### Overload protection

The machine uses pulsation to warn you of an approaching overload. If the load is not reduced the motor will shut off, to prevent overheating. Elgard™ increases productivity and extends product life.



### Durable and ergonomic design

Durable and shock-proof, designed to protect the electronics. Easy to carry and install thanks to low weight and ergonomic design.

- Softstart™
- Barriers
- Channels, pipes and cables

### Reliable gearbox

Watercooled 3 speed gearbox for optimal drilling performance and longer service intervals.



SPECIFICATIONS



Water connector	G 1 / 4"
Weight	7 kg
Product size length	438 mm
Product size width	104 mm



Electronic product	Yes
Frequency	60 Hz
Voltage	100-120 V
Rated input power	1.85 kW



Drill bit diameter handheld, max	80 mm
Drill bit diameter with stand, max	150 mm
Recommended drill bit diameter, min	0 mm



Sound power level, guaranteed (LWA)	108 dB(A)
Sound power level, measured	107 dB(A)
Sound pressure level at operators ear	93 dB(A)

Specifications

Water pressure, max	8 bar
Mounting collar	60 mm
Spindle thread, inner	5 / 8" - 11 UNC
Spindle thread, outer	1 1/4" 7 UNC
Number of gearbox speeds	3