

11. SPECIFICATIONS

DSR114

Internal Battery Type.....	Sealed, Maintenance Free, AGM, Lead-Acid
Nominal Voltage.....	12V DC
Capacity.....	22Ah
DC Power Output (Maximum Continuous Load).....	12V DC/15A
Peak Amps.....	2200
Cranking Amps.....	525
Cold Cranking Amps.....	350
Battery Hookup Cables.....	4 AWG, 60" (152 cm)
Dimensions (H x W x D).....	16.7" x 12.9" x 5.5" (42.5 x 33 x 14 cm)
Weight.....	18.73 lbs (8.5 kg)

DSR115

Internal Battery Type.....	Sealed, Maintenance Free, AGM, Lead-Acid
Nominal Voltage.....	12V/24V DC
Capacity.....	(2) 22Ah
DC Power Output (Maximum Continuous Load).....	12V DC/15A
Peak Amps.....	4400
Cranking Amps.....	750 (12V) / 475 (24V)
Cold Cranking Amps.....	525 (12V) / 350 (24V)
Battery Hookup Cables.....	2 AWG, 60" (152 cm)
Dimensions (H x W x D).....	16.7" x 12.9" x 7.4" (42.5 x 33 x 19 cm)
Weight.....	39.68 lbs (18 kg)

Charger

Input voltage.....	120V AC @ 60Hz, 0.5A
Output voltage.....	12V DC
Output current rating.....	2A

12. REPLACEMENT PARTS/ACCESSORIES

Male-to-male accessory cable.....	94500109
DSR2 Charger.....	2299003063CZ
Replacement battery (DSR115 uses 2).....	5799000010Z