| Technical Specific | ations For Mod | el SC-4 Extractor | |
|------------------------------|---|---|--|
| Storage Dimensions / Weight: | | Width: 12" Height: 25" Depth: 19.5" / 46 lbs. | |
| Construction: | | High Impact Rotationally Molded Polyethylene, Cast Aluminum, Stainless Steel | |
| Recovery Tank: | | 4 Gal. Built-In Removable Easy Pour Recovery Tank for Filling & Emptying | |
| Solution Tank: | | 4 Gal. with Pump Protecting Dual Filtration | |
| Solution Tube: | | Solution Level-Drain Tube for User Convenience | |
| Handle: | | Four Position Adjustable and Collapsible for Storage and Transport | |
| Vacuum Lid: | | Hinged, Dual Sight Glass, Protective Vacuum Filter | |
| Vacuum Motor: | | Ametek High Performance Two-Stage / 108" Water Lift / 112 CFM | |
| Pump: | | 35 PSI / .85 GPM | |
| Brush Motor: | | 2,500 RPM Permanent Magnate DC | |
| Brush: | | 1,200 RPM Three Row Chevron, Stainless Shaft, Shock Mounted Bearings | |
| Brush Housing: | | Heavy Duty Cast Aluminium, Stainless Bearings, Kevlar Reinforced Gear Belt | |
| Vacuum Nozzle: | | Heavy Duty Cast Aluminum, with Stainless or Delrin Glide for Hard Surface | |
| Instructions: | | Easy to Read Operating Instructions Printed on the Machine | |
| Accessories: | | Vacuum and Pump Accessory Ports for Hand Tools and Floor Wands | |
| Co Co UL CS | ER SAFETY Informs To STD 1017 And A STD C22.2 D. 243-01 | Self-contained carpet extractors feature a high speed chevron brush to loosen ground in soil. The brush works on types of carpets with no adjustment required. Well balanced rotational molded polyethylene construction for ease of operation and years of reliable top performance. | Optional Quick Dry and Dual Surface Cleaning: Uses Less Water Dries Fast Less Emptying & Refilling |





Heavy Duty Cast Aluminum Vacuum Nozzle and Brush Housing with Powerful Chevron Brush

Shipp Cleaning Systems 1360 Business Center Drive Conyers, Georgia 30094 800-962-1723 www.shippcleaningsystems.com



Made with pride in the U.S.A.

Keep it SHIPP Shape!